



ASEPTIC WASHING MACHINE, 50 KG AS 500

Ref: 0920.12.010

Grandimpianti

Programmable control microprocessor.

Stainless steel body, tub and drum.

Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).

Opposing doors with barrier avoiding any possible contact between clean and soiled laundry.

Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.

Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.

Available in steam version. Contact us!

The data are related to the 60° C wash cycle reported on the standard ISO 9398

FEATURES

Capacity Load, min. - max. (1:10 / 1:9)	50 kg / 55.6 kg
Capacity drum	500 l - Ø 775x1060 mm
Doors per side	1
Pockets	1
Spin R.P.M	41 - 900
Spin G Factor	350
Noise	49.7 dB - 69.9 dB
Dimensions (WDH)	1566x980x1700 mm
Weight net	1130 kg
Weight gross	1280 kg
Heating power - electric standard	48 kW
Motor - electronic control	Yes
Motor - power	10.06 kW
Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Consumption - hot water	244 l
Consumption - warm water	168 l (133 l eco mode)
Control - PLC	Yes
Electric water drain	2x 3"

Chemical supply - soap hopper	Yes
-------------------------------	-----

Chemical supply - ready for liquid soap supply	Yes
--	-----