

## ASEPTIC WASHING MACHINE, 90 KG AS 90

Ref: 0920.12.013  
Grandimpianti



Programmable control microprocessor.  
Stainless steel body, tub and drum.  
Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).  
Opposing doors with barrier avoiding any possible contact between clean and soiled laundry.  
Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.  
Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.  
Available in steam version. Contact us!  
The data are related to the 60° C wash cycle reported on the standard ISO 9398

### FEATURES

|                                              |                            |
|----------------------------------------------|----------------------------|
| Capacity Load, min. - max. (1:10 / 1:9)      | 90 kg / 100 kg             |
| Capacity drum                                | 900 l - Ø 1000x1150 mm     |
| Doors per side                               | 1                          |
| Pockets                                      | 2                          |
| Door                                         | 765x340 mm                 |
| Spin R.P.M                                   | 36 - 800                   |
| Spin G Factor                                | 358                        |
| Noise                                        | < 85 dB                    |
| Dimensions (WDH)                             | 2275x1615x1805 mm          |
| Weight net                                   | 2810 kg                    |
| Weight gross                                 | 2970 kg                    |
| Heating power - supplied with hot water only | Opcional                   |
| Heating power - electric standard            | 72 kW                      |
| Motor - electronic control                   | Yes                        |
| Motor - power                                | 11 kW                      |
| Power supply - standard                      | 380 - 415 V 3 N ~ 50/60 Hz |
| Consumption - hot water                      | 242 l                      |
| Consumption - warm water                     | 966 l                      |

|                                                |                   |
|------------------------------------------------|-------------------|
| Control - PLC                                  | Yes               |
| Electric water drain                           | 1x 5 <sup>2</sup> |
| Chemical supply - soap hopper                  | Yes               |
| Chemical supply - ready for liquid soap supply | Yes               |