

REFRIGERATED COUNTER, 535 L GTRS-250 HC

Ref: 0161.462.005A
 Magnus



High quality austenitic stainless steel interior and exterior, except for galvanised back. Rounded corners inside and on the worktop. Injected polyurethane insulation with 40 kg/m³ density, free CFC. Ventilated cold. Electronic and digital control system of temperature and defrost. Doors with self-closing system and fixed opening. Automatic evaporation of defrosting water. Evaporator with epoxy anti-corrosion coating. Waste liquids are drained through the cleaning hole at the bottom of the cabinet. Height adjustable stainless steel feet.

Temperature range: -2 / +8 °C.

100 mm hygienic splashback.

R-290 Refrigerant.

Sliding group for easy cleaning and maintenance.

Includes 1 grid per door.

Note: The image displayed is the 3-door model.

FEATURES

| | |
|------------------------|------------------|
| Dimensions (WDH) | 2542x600x850 mm |
| Power | 0.332 kW |
| Cooling power | 0.593 kW |
| Power supply | 230V/1/50Hz |
| Capacity (gross / net) | 535 / 307 l |
| Doors | 4 |
| Weight | 130 kg |
| Energy class | D |
| Packaging dimensions | 680x2660x1060 mm |
| Gross weight | 152 kg |