GAS TUMBLE DRYER, 11 KG GDZ 275G

Ref: 0911.12.078 Grandimpianti

Second temperature probe, as standard.

Control of real drum rotation by sensors (aluminum coated drum).

Redundant security: on drum opening, on the inspection filter panel, on the exhaust temperature.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Up to 10 drying programs, to manage manually and optimize consumptions. Times and temperatures automatically managed.

Electronic control G-Wiz® : 10 possibility to create and customize drying programs.

Big air flow.

Extremely silent

Exhaust air filtered by inox filter.

Inox filter, as standard

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

Self-Service program, as standard.

FE	AT	UR	ES

Capacity load (1:25); (1:20); (1:18)	11 kg; 14 kg; 15.3 kg
Capacity drum	275 I - Ø 740x640 mm
Door	Ø 612 mm
Drum rotation	40
Noise	< 55 dB
Dimensions (WDH)	795x920x1590 mm
Weight net	205 kg





Weight gross	215 kg
Control - G-WIZ	Yes
Drum/vacuum motor - Power	0.75 kW
Power supply	380 - 415 V 3 N ~ 50/60 Hz
Washing machines - ideal with	GWH105
Heating power - Gas (double stage)	13 - 18 kW
Consumption of evaporation	8.7 l/h
Electric consumption	0.5 kW/l
Natural gas G20 consumption	1.9 m3/h
LPG gas G31 consumption	0.8 kg/h
Gross weight	215 kg