

ASEPTIC WASHING MACHINE, 18 KG GA 18

Ref: 0920.12.006
 Grandimpianti



Programmable control microprocessor.

Stainless steel body, tub and drum.

Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).

Oposing doors with barrier avoiding any possible contact between clean and soiled laundry.

Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.

Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.

Available in steam version. Contact us!

The data are related to the 60° C wash cycle reported on the standard ISO 9398

FEATURES

Capacity Load, min. - max. (1:10 / 1:9)	18 kg / 20 kg
Capacity drum	180 l - Ø 750x409 mm
Doors per side	1
Pockets	1
Door	376x325 mm
Spin R.P.M	42 - 939
Spin G Factor	370
Noise	<70 dB
Dimensions (WDH)	900x1145x1455 mm
Weight net	430 kg
Weight gross	485 kg
Heating power - supplied with hot water only	Optional
Heating power - electric standard	12 kW

Motor - electronic control	Yes
Motor - power	2.2 kW
Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Consumption - hot water	38.5 l
Consumption - warm water	38.5 l
Consumption - cold water	77 l
Consumption - cycle length	56 min
Control - PLC	Yes
Electric water drain	1x 3 $\frac{1}{2}$ "
Chemical supply - soap hopper	Yes
Chemical supply - ready for liquid soap supply	Yes
Gross weight	485 kg