

GAS COMBI OVEN (DIRECT STEAM), 20XGN1/1 MC 20.1 G

Ref: 1101.810.017 Magnus

Body and chamber in stainless steel.

Chamber with rounded corners and bottom in diamant form that allows an easy draining of condensation liquids.

Convection mode with percentage humidity regulation: from 20 to 270 $^{\circ}$ C; steam mode: from 20 to 100 $^{\circ}$ C; core probe: from 20 to 99 $^{\circ}$ C; Delta T function: from 30 to 150 $^{\circ}$ C.

Longitudinal grid/containers entrance.

150 pre-stored programs with possibility for the user to add 150 more. Programs up to 6 steps.

Cook & Hold function.

Removable gasket around the door for simple and throughout cleaning.

Perfect thermic insulation with double glass door.

Ergonomic and heat insulated handle.

Door with micro switch that automatically turns off the ventilators when door is opened.

USB connection.

Core probe with Deta T function.

Automatic programs.

Automatic preheating function.

Fans with inverse rotation and 2 ventilation speed selectable.

Automatic washing with tablets.

Quick cooling down of the cooking chamber.

Supplied with trolley, GN1/1 grid and 1 package of tablet detergent.



300
20x GN1/1
65 mm
970x1103x1880 mm
29 kW + 1.5 kW (Eletric)
230V 1N~ 50/60Hz
2
3.069 m3/h (G20)
2.287 kg/h (G30)/ (G31)
440 kg