

BLAST CHILLER AND SHOCK FREEZER FOR 20X GN2/1 TROLLEY WITH AIR REMOTE UNIT CMP-202 PLUS

Ref: 0165.462.005
 Magnus

Capacity for 20 trays GN2/1 trolley.

Forced draught refrigeration with optimised air circulation

R-404A refrigerant.

Electronic and digital control system of temperatures and defrost.

Climatic class T (Ambient temperature: +43 °C).

Electronic thermostat programmable by time, temperature probe and phases (up to 10 programs).

100 mm of injected polyurethane insulation, free CFC.

AISI 304 Stainless steel interior and exterior.

Ergonomic handle and magnetic closure.

Depth with 90° door: 2240 mm.

HACCP traceability system with alarm and temperature log, and the option of extracting data.

Alarm to avoid long time door openings.

Airtight/scroll/semi airtight/ compressor with fan-assisted condenser.

Heated core probe.

Remote unit with air condensation.

Equipped with USB input as standard.



FEATURES

| | |
|--------------------------|---------------------------------|
| Dimensions (WDH) | 1700x(1320+135)x2220 mm |
| Chamber dimensions (WDH) | 770x1170x1900 mm |
| Power | 0.85 kW (230V) + 8.45 kW (400V) |
| Cooling power | 13.58 kW |
| Power supply | 400/3/50Hz |

| | |
|--|-------------------------------------|
| Cooling (+90 to + 3°C) cycle 90 min. | 210 kg |
| Freezing (+90 to -18°C) cycle 240 min. | 135 kg |
| Weight | 420 kg (un.) + 214 kg (remote unit) |
| Gross weight | 0,01 kg |