

## BLAST CHILLER AND SHOCK FREEZER FOR 20X GN2/1 TROLLEY WITH AIR REMOTE UNIT (UP TO 25 M) CM-202

Ref: 0165.462.009 Magnus

Capacity for 20 trays GN2/1 trolley.

Forced draught refrigeration with optimised air circulation

R-404A refrigerant.

Electronic and digital control system of temperatures and defrost.

Climatic class T (Ambient temperature: +43 °C).

Electronic thermostat programmable by time, temperature probe and phases (up to 10 programs).

100 mm of injected polyurethane insulation, free CFC.

AISI 304 Stainless steel interior and exterior.

Ergonomic handle and magnetic closure.

Depth with 90° door: 2240 mm.

HACCP traceability system with alarm and temperature log, and the option of extracting data.

Alarm to avoid long time door openings.

Airtight/scroll/semi airtight/ compressor with fan-assisted condenser.

Heated core probe.

Remote unit with air condensation.

Equipped with USB input as standard.

FEATURES	
Dimensions (WDH)	1700x(1320+135)x2220 mm
Chamber dimensions (WDH)	770x1170x1900 mm
Power	0.85 kW (230V) + 6.5 kW (400V)
Cooling power	10.53 kW



Power supply	400/3/50Hz
Cooling (+90 to + $3^{\circ}$ C) cycle 90 min.	150 kg
Freezing (+90 to -18°C) cycle 240 min.	100 kg
Weight	420 kg (un.) + 205 kg (remote unit)