

## ELECTRIC TUMBLE DRYER WITH WAVY® CONTROL, 18 KG - THREE-PHASE GD 450E

Ref: 0911.12.073A  
 Grandimpianti

Drum inversion and second temperature probe, as standard.

Electronic control Wavy®: user interface adaptable to user needs and skills; unlimited possibility to create and customize programs. Possibility to record all working data.

Unlimited programs, to manage manually and optimize consumptions. Times and temperatures automatically managed.

Control of real drum rotation by sensors (aluminum coated drum).

Redundant security: on drum opening, on the inspection filter panel, on the exhaust temperature.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and quick maintenance: ergonomic position of internal components easy to be reached.

Big air flow.

Extremely silent

Exhaust air filtered by inox filter.

Inox filter, as standard

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

Self-Service program, as standard.



### FEATURES

|                                      |                       |
|--------------------------------------|-----------------------|
| Capacity load (1:25); (1:20); (1:18) | 18 kg; 22.5 kg; 25 kg |
| Capacity drum                        | 450 l - Ø 940x640 mm  |
| Door                                 | Ø 612 mm              |
| Drum rotation                        | 40                    |
| Noise                                | < 55 dB               |
| Dimensions (WDH)                     | 970x990x1810 mm       |

|                                   |                            |
|-----------------------------------|----------------------------|
| Weight net                        | 287 kg                     |
| Weight gross                      | 302 kg                     |
| Control - WAVY                    | Yes                        |
| Drum motor - Power                | 0.55 kW                    |
| Vacuum motor - Power              | 1.1 kW                     |
| Power supply                      | 380 - 415 V 3 N ~ 50/60 Hz |
| Washing machines - ideal with     | GWH180                     |
| Heating power - Electric standard | 15 + 15 kW                 |
| Consumption electric energy       | 12.6 kW/h                  |
| Consumption of evaporation        | 12.55 l/h                  |
| Packaging dimensions              | 1090x1180x1860 mm          |
| Gross weight                      | 300 kg                     |