ELECTRIC FLATWORK DRYER-IRONER Ø 500X2000MM GC 2050 E

Ref: 0913.12.025 Grandimpianti

Structure in painted sheet and plastic coated sheet metal.

Easy to use 7 ? touch screen with 37 languages available.

Front-service type to be used by one or two operators. The rotary drying press can be installed against a wall.

Roller ironing speed adjustable between 1m/min. and 8m/min. thanks to the motor controlled with inverter technology.

Finger-saving fillet protects the operator in case of mishandling.

Manual device to move the roller and remove the washing in case of power failure.

Steam version, on request.

* with length folder or pass through (optional).

** with length folder (optional).

*** with length folder and pass through (optional).

| FEATURES | |
|------------------|------------------------------------|
| Dimensions (WDH) | 2845x1070(*1417)x1420 mm |
| Power supply | 400V/3/50 Hz |
| Motor power | 0.62 kW (**+0.56 kW /***+0.74 kW) |
| Capacity | 50 - 70 kg/h |
| Roller | Ø 500x2000 mm |
| Speed roller | 1 - 8 m/min |
| Extraction power | 600 m3/h |
| Flue outlet | 1x Ø 153 mm |
| Total power | 32.12 kW (**32.68 kW /***32.86 kW) |
| Heating power | 31.5 kW |



