

GAS FLATWORK DRYER-IRONER Ø 500X2000MM GC 2050 G

Ref: 0913.12.026 Grandimpianti

Structure in painted sheet and plastic coated sheet metal.

Easy to use 7 Ptouch screen with 37 languages available.

Front-service type to be used by one or two operators. The rotary drying press can be installed against a wall.

Roller ironing speed adjustable between 1m/min. and 8m/min. thanks to the motor controlled with inverter technology.

Finger-saving fillet protects the operator in case of mishandling.

Manual device to move the roller and remove the washing in case of power failure.

Electronic device controls start and gas flame.

Steam version, on request.

* with length folder or pass through (optional).

** with length folder (optional).

*** with length folder and pass through (optional).

| FEATURES | |
|-------------------------|-----------------------------------|
| Dimensions (WDH) | 2845x1070(*1417)x1420 mm |
| Power supply | 400V/3/50 Hz |
| Motor power | 0.62 kW (**+0.56 kW /***+0.74 kW) |
| Capacity | 50 - 70 kg/h |
| Roller | Ø 500x2000 mm |
| Speed roller | 1 - 8 m/min |
| Extraction power | 600 m3/h |
| Flue outlet | 1x Ø 153 mm |
| Gas thermal power | 40 kW |
| Natural gas consumption | 4.2 m3/h |



| GPL gas consumption | 3.1 kg/h |
|----------------------|-----------------------------------|
| Total electric power | 0.62 kW (**+0.56 kW /***+0.74 kW) |