



## ASEPTIC WASHING MACHINE, 24 KG GA 24

Ref: 0920.12.007  
Grandimpianti

Programmable control microprocessor.  
Stainless steel body, tub and drum.  
Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).  
Opposing doors with barrier avoiding any possible contact between clean and soiled laundry.  
Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.  
Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.  
Available in steam version. Contact us!  
The data are related to the 60° C wash cycle reported on the standard ISO 9398

### FEATURES

Capacity Load, min. - max. (1:10 / 1:9)	24 kg / 26.7 kg
Capacity drum	240 l - Ø 750x544 mm
Doors per side	1
Pockets	1
Door	496x325 mm
Spin R.P.M	42 - 939
Spin G Factor	370
Noise	<70 dB
Dimensions (WDH)	1020x1145x1455 mm
Weight net	460 kg
Weight gross	515 kg
Heating power - supplied with hot water only	Opcional
Heating power - electric standard	18 kW
Motor - electronic control	Yes
Motor - power	3 kW
Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Consumption - hot water	51.4 l
Consumption - warm water	51.4 l

Consumption - cold water	102.7 l
Consumption - cycle length	58 min
Control - PLC	Yes
Electric water drain	1x 3 <sup>2</sup>
Chemical supply - soap hopper	Yes
Chemical supply - ready for liquid soap supply	Yes