



ASEPTIC WASHING MACHINE, 28 KG GA 28

Ref: 0920.12.008
 Grandimpianti

Programmable control microprocessor.
 Stainless steel body, tub and drum.
 Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).
 Opposing doors with barrier avoiding any possible contact between clean and soiled laundry.
 Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.
 Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.
 Available in steam version. Contact us!
 The data are related to the 60° C wash cycle reported on the standard ISO 9398

FEATURES

Capacity Load, min. - max. (1:10 / 1:9)	28 kg / 31.1 kg
Capacity drum	280 l - Ø 750x639 mm
Doors per side	1
Pockets	1
Door	496x325 mm
Spin R.P.M	42 - 914
Spin G Factor	350
Dimensions (WDH)	1130x1145x1455 mm
Weight net	490 kg
Weight gross	550 kg
Heating power - supplied with hot water only	Opcional
Heating power - electric standard	21.9 kW
Motor - electronic control	Yes
Motor - power	3 kW
Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Consumption - hot water	60 l
Consumption - warm water	60 l
Consumption - cold water	120 l

Control - PLC	Yes
Electric water drain	1x 3 ²
Chemical supply - soap hopper	Yes
Chemical supply - ready for liquid soap supply	Yes