



ASEPTIC WASHING MACHINE, 36 KG AS 360

Ref: 0920.12.009
Grandimpianti

Programmable control microprocessor.
Stainless steel body, tub and drum.
Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).
Opposing doors with barrier avoiding any possible contact between clean and soiled laundry.
Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.
Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.
Available in steam version. Contact us!
The data are related to the 60° C wash cycle reported on the standard ISO 9398

FEATURES

Capacity Load, min. - max. (1:10 / 1:9)	36 kg / 40 kg
Capacity drum	360 l - Ø 775x764 mm
Doors per side	1
Pockets	1
Spin R.P.M	41 - 900
Spin G Factor	350
Noise	43.9 dB - 68 dB
Dimensions (WDH)	1270x980x1700 mm
Weight net	960 kg
Weight gross	1090 kg
Heating power - electric standard	36 kW
Motor - electronic control	Yes
Motor - power	5.36 kW
Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Consumption - hot water	190 l
Consumption - warm water	121 l (93 l eco mode)
Control - PLC	Yes
Electric water drain	2x 3 $\frac{1}{2}$ "

Chemical supply - soap hopper

Yes

Chemical supply - ready for liquid soap supply

Yes
