

## ASEPTIC WASHING MACHINE, 70 KG AS 700

Ref: 0920.12.011  
 Grandimpianti



Programmable control microprocessor.  
 Stainless steel body, tub and drum.  
 Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).  
 Opposing doors with barrier avoiding any possible contact between clean and soiled laundry.  
 Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.  
 Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.  
 Available in steam version. Contact us!  
 The data are related to the 60° C wash cycle reported on the standard ISO 9398

### FEATURES

Capacity Load, min. - max. (1:10 / 1:9)	70 kg / 77.8 kg
Capacity drum	700 l - Ø 775x(2x 742) mm
Doors per side	2
Pockets	2
Spin R.P.M	41 - 900
Spin G Factor	350
Noise	47.8 dB - 69 dB
Dimensions (WDH)	2032x980x1700 mm
Weight net	1310 kg
Weight gross	1470 kg
Heating power - electric standard	60 kW
Motor - electronic control	Yes
Motor - power	10.06 kW
Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Control - PLC	Yes
Electric water drain	2x 3 $\frac{1}{2}$ "
Chemical supply - soap hopper	Yes
Chemical supply - ready for liquid soap supply	Yes