

ASEPTIC WASHING MACHINE, 90 KG AS 90

Ref: 0920.12.013
Grandimpianti



Programmable control microprocessor.
Stainless steel body, tub and drum.
Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).
Opposing doors with barrier avoiding any possible contact between clean and soiled laundry.
Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.
Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.
Available in steam version. Contact us!
The data are related to the 60° C wash cycle reported on the standard ISO 9398

FEATURES

Capacity Load, min. - max. (1:10 / 1:9)	90 kg / 100 kg
Capacity drum	900 l - Ø 1000x1150 mm
Doors per side	1
Pockets	2
Door	765x340 mm
Spin R.P.M	36 - 800
Spin G Factor	358
Noise	< 85 dB
Dimensions (WDH)	2275x1615x1805 mm
Weight net	2810 kg
Weight gross	2970 kg
Heating power - supplied with hot water only	Opcional
Heating power - electric standard	72 kW
Motor - electronic control	Yes
Motor - power	11 kW
Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Consumption - hot water	242 l
Consumption - warm water	966 l

Control - PLC	Yes
Electric water drain	1x 5 ²
Chemical supply - soap hopper	Yes
Chemical supply - ready for liquid soap supply	Yes