

## ASEPTIC WASHING MACHINE, 110 KG AS 110

Ref: 0920.12.014  
 Grandimpianti



Programmable control microprocessor.  
 Stainless steel body, tub and drum.  
 Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).  
 Opposing doors with barrier avoiding any possible contact between clean and soiled laundry.  
 Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.  
 Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.  
 Available in steam version. Contact us!  
 The data are related to the 60° C wash cycle reported on the standard ISO 9398

### FEATURES

Capacity Load, min. - max. (1:10 / 1:9)	110 kg / 122.2 kg
Capacity drum	1100 l - Ø 1100x1200 mm
Doors per side	1
Pockets	3
Door	765x340 mm
Spin R.P.M	35 - 754
Spin G Factor	350
Noise	< 85 dB
Dimensions (WDH)	2325x1615x1855 mm
Weight net	2990 kg
Weight gross	3150 kg
Heating power - supplied with hot water only	Opcional
Heating power - electric standard	96 kW
Motor - electronic control	Yes
Motor - power	15 kW
Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Consumption - hot water	296 l
Consumption - warm water	1179 l

Control - PLC	Yes
Electric water drain	1x 5 <sup>2</sup>
Chemical supply - soap hopper	Yes
Chemical supply - ready for liquid soap supply	Yes