

ASEPTIC WASHING MACHINE, 140 KG AS 140

Ref: 0920.12.015
 Grandimpianti



Programmable control microprocessor.
 Stainless steel body, tub and drum.
 Painted body for AS 360, AS 500 and AS 700 models (stainless steel on request).
 Opposing doors with barrier avoiding any possible contact between clean and soiled laundry.
 Side stabilisers ensure best machine stability in all possible use conditions and guarantee slower wear on dampening system.
 Supplied optional: three-phase section circuit-breaker, emergency push-button, isolation transformer, water supply piping, drain pipe, steam supply pipe.
 Available in steam version. Contact us!
 The data are related to the 60° C wash cycle reported on the standard ISO 9398

FEATURES

Capacity Load, min. - max. (1:10 / 1:9)	140 kg / 155.5 kg
Capacity drum	1400 l - Ø 1200x1250 mm
Doors per side	1
Pockets	3
Door	765x440 mm
Spin R.P.M	32 - 720
Spin G Factor	350
Noise	< 80 dB
Dimensions (WDH)	2435x1805x2075 mm
Weight net	3550 kg
Weight gross	3760 kg
Heating power - supplied with hot water only	Opcional
Heating power - electric standard	96 kW
Motor - electronic control	Yes
Motor - power	18.5 kW
Power supply - standard	380 - 415 V 3 N ~ 50/60 Hz
Consumption - hot water	346 l
Consumption - warm water	1379 l

Control - PLC	Yes
Electric water drain	1x 5 ²
Chemical supply - soap hopper	Yes
Chemical supply - ready for liquid soap supply	Yes