

## BAIN MARIE COUNTER WITH STORAGE, 3X GN1/1, 150 MM SBMR-311

Ref: 1186.462.019

Magnus



Models with heated storage (forced ventilation).

Bain-marie indirect water heating with hidden silicon resistors attached to the bottom of the well. Silicon resistors improve heating performance and reduce electrical consumption.

Stamped well, with rounded edges for easy cleaning.

The regulation and control of the bain-marie temperature is carried out by means of an analogue thermometer and a thermostat.

Counters with heated storage, the storage temperature is controlled with a separate thermostat.

Operating pilot light.

Double-wall sliding doors, with an injected CFC-free, ecological polyurethane 40 Kg/m<sup>3</sup> density isolation, in counters with heated storage.

Water inlet and drainage taps included.

Height-adjustable, robust feet.

External and internal structure made of AISI-304 18/10 stainless steel.

Glass foodshields and glass shelving can be assembled on top of the counter as optional.

The front panel can be coated with different colors.

Tray slide supplied disassembled from the counter. To be ordered separately as an option.

Containers not included.

Important note: Well must contain water when bain-marie is started.

### FEATURES

Dimensions (WDH) 1200x700x850 mm

Power 3.5 kW

Power supply 230V/1/50 Hz

Capacity 3x GN1/1, 150 mm

Temperature +30 °C / +90 °C

Type With storage