

ELECTRIC TUMBLE DRYER, 62 KG - THREE-PHASE GD 1550 E

Ref: 0911.12.114
Grandimpianti



Electronic control Wavy®: user interface adaptable to user needs and skills; unlimited possibility to create and customize programs. Possibility to record all working data.

Unlimited programs, to manage manually and optimize consumptions. 10 already programmed. Times and temperatures automatically managed.

Reversing drum function to assure always a uniform drying action even with big linen.

Drum made of stainless steel AISI 430.

Outler air filtered with double inox filter mesh.

The average energy consumption is of 1 kW/kg.

Porthole at 830-840 mm from the floor to allow the direct approach with the trolley.

Drum door opening 180°: easy loading and unloading process placing a trolley against the machine.

Easy and frontal access to the lint filter system.

Thermal insulation: 25 mm ceramic fiber to assure low heating power and low exhaust air temperature.

FEATURES

Capacity load (1:25); (1:20)	40 kg / 50 kg
Capacity drum	1550 l
Door	Ø 800 mm
Drum rotation	25 - 40 rpm
Noise	< 65 db
Dimensions (WDH)	1310x2045x2200 mm
Weight net	530 kg
Weight gross	560 kg
Control - WAVY	Yes
Ideal with washing machine	WFP80
Electric power	72 kW
Electric power - Drum motor	1.5 kW
Electric power - Vacuum motor	2.2 kW
Power supply	380 - 415 V 3 N ~ 50/60 Hz
Evaporation capacity	54 l/h

Electric consumption

63 kWh

Cycle length

55 min.
