

STEAM TUMBLE DRYER, 15 KG - THREE-PHASE EBV 15

Ref: 0911.12.033
 Grandimpianti



Automatic inversion of the drum rotation with one inversion per minute.

Stainless steel drum and plasticized sheet-steel structure (Skin plate).

Air recycling system enables remarkable energy recovery.

Wide opening facilitates laundry loading.

Easy to open inspectable lint filter, made by stainless steel net.

Filter condition (% of dirtiness detected) showed on display.

Overload control; soft start (only EB 10 and EB 15 models); direct transmission instead of chain transmission; overcurrent protection switch on the motor.

Second temperature probe (only EB 41 model).

Every cycle is completed by an automatically controlled cooling stroke (permanent press), for an easy remover of the linen.

Optional: Payment system - Electromechanical coin meter, electronic coin meter and central payment system (only EB 10 and EB 15 models).

FEATURES

Capacity load (1:25); (1:20)	12 kg; 15 kg
Capacity drum	300 l - Ø 761x660 mm
Door	Ø 612 mm
Drum rotation	20 - 80
Noise	< 64 dB
Dimensions (WDH)	795x970x1290 mm
Weight net	134 kg
Weight gross	153 kg
Control - G400 DRY	Yes
Drum motor - Power	0.5 kW

Power supply 380 - 415 V 3 N ~ 50/60 Hz

Consumption evaporation 5 - 7 l/h

Consumption steam 30 kg/h

Consumption steam pressure 400/600 kPA - 4/6 bar
