

## STAINLESS STEEL POTATO PEELER 30 KG, THREE-PHASE PI-30 TR

Ref: 0703.10.030  
 Sammic



Structure made of stainless steel.  
 Lateral stirrers covered with silicon carbide abrasives (approved by NSF).  
 Aluminium base plate lined with silicon carbide abrasive (approved by NSF), easily removable for cleaning purpose.  
 Auto-drag of waste to the drain.  
 Energy efficiency thanks to engine optimization.  
 Lifiable transparent polycarbonate cover, complete with locking and safety device.  
 Aluminium door with hermetic seal and safety device.  
 Control board with IP65 protection. Improved reliability against humidity and water splash.  
 Water inlet with non-return system.  
 PI-30: Water inlet system fitted with electric valve.  
 Auxiliary contact for external electric valve.  
 Timer 0-6 minutes and continuous operation.  
 Support not included.

### FEATURES

|                             |                 |
|-----------------------------|-----------------|
| Dimensions (WDH)            | 622x760x1002 mm |
| Dimensions with Stand (WDH) | 546x760x1255 mm |
| Power                       | 0.73 kW         |
| Power supply                | 400V/3/50 Hz    |
| Maximum production          | 720 kg/h        |
| Capacity per load           | 30 kg per cycle |
| Weight                      | 60 kg           |
| Packaging dimensions        | 670x820x1190 mm |
| Gross weight                | 70 kg           |